

# LUBRANIL<sup>®</sup> N 20

## Application:

LUBRANIL<sup>®</sup> N 20 is a waterbased dispersion for pasty plasters and waterborne dispersion paints. LUBRANIL<sup>®</sup> N 20 is very suitable for polymeric, silicate and silicone based systems.

## Properties and advantages:

- Prolongs the open time
- Improves the elasticity of the coating
- Prevents from cracks and rents
- Plastification
- Improves the workability of the plaster
- Assists to reduce pinholes
- Free of any solvents, free of VOC

## Technical data:

Appearance:	white, liquid
Active content:	20 ± 2 %
Ionity:	non-ionic
pH-value:	7 ± 1
Density:	0,95 g/cm <sup>3</sup>
Dilution:	in water in any ratio

## Recommended dosage:

LUBRANIL<sup>®</sup> N 20 is used in quantities of 0,4 - 2 %, as it is, based on total formula. It should be incorporated together with the binder.

Before use the product should be stirred.

## Transport and storage:

Our dispersions are sensitive to frost!  
To be stored and transported between + 10° C and + 35° C.  
Maximum storage time 6 months in originally closed packing.

## Packing:

drums with 150 kg  
containers with about 1.000 kg

Mannheim, November 2009

Notice: This data sheet is based on our current knowledge and experience. In view of the individual factors that may affect processing and application, this data does not relieve users from the responsibility of carrying out their own tests and experiments, neither do they imply any legally binding assurance of certain products properties. Also no guarantee is given on performance. Existing industrial commercial protective laws have to be considered by the recipient.

This datasheet is replacing all former existing versions, statements and certifications.